Addition of storey Dohlenweg 28+30, Zürich

2021





Centrally located in Zurich Oerlikon, the building offers modern and appealing rental apartments after total renovation and addition of new floors.

The project

The existing building was completely renovated and at the same time one floor was added. While the existing building is made of reinforced concrete, the extension was realized in a lightweight timber construction.

The construction


In the case of the addition in wood, the exterior walls are made of a stud wall. On the outside, the stud wall is provided with external thermal insulation and finished with an abrasion. The roof is formed by hollow box elements that support the flat roof structure.

The challenge


The exterior walls should be as slender as possible. The load transfer points are very punctual over the whole extension, due to the existing building.







Roof edge closure



Connection of exterior wall to existing building

Construction Data

- Three-layer glulam 36 m³
- Glued laminated timber 44 m³
- gypsum fiberboards 28 m³
- Frame construction scantlings 33 m³
- OSB 3 m³

Services of Timbatec

- SIA Phase 31 Preliminary design
- SIA Phase 32 Construction project
- SIA Phase 41 Tendering and comparison of offers
- SIA Phase 51 Implementation project
- SIA Phase 52 Execution
- Statics and construction

Owner

Zurich Investment Foundation 8045 Zurich

Client

CORTI Total Services AG 8406 Winterthur

Architect

Dachtler Partner AG 8036 Zurich

Timber construction engineer

Timbatec Holzbauingenieure (Schweiz) AG Zurich 8005 Zurich

Civil Engineer

Basler & Hofmann AG 8032 Zurich

GU/TU, construction management, photography

CORTI Total Services AG 8406 Winterthur

Building physics

Wichser Akustik & Bauphysik AG 8052 Zurich

